



SeniorSoft®



SNS-Q2B

Thermal Receipt Printer

- Paper shortage alarm
- Support NV logo printing
- With saving power function
- Support Bluetooth dual mode
- Support multiple 1D&2D code printing
- Compatible with Windows/IOS/Android



Store



Hospital



Café



Logistics



SeniorSoft®

📍 สำนักงานใหญ่

☎ 0-2692-5899

📍 สาขา เอ็ม บี เค เซ็นเตอร์

☎ 0-2048-4500

📍 สาขา ซีกอนสแควร์ ศรีนครินทร์

☎ 0-2656-6089

📍 สาขา เซียร์ รังสิต

☎ 0-2992-6476-77

📍 สาขา เชียงใหม่

☎ 053-850-444

📍 สาขา อุดรธานี

☎ 042-247-455

📍 สาขา หาดใหญ่

☎ 074-246-955-6



@seniorsoft www.SeniorSoft.com




SeniorSoft Development Q



SNS-Q2B

Thermal Receipt Printer



Printing		SNS-Q2B	
Printing method	Direct thermal		
Paper width	58mmΦ40mm		
Print width	48mm		
Line spacing	3.75mm (Adjustable by commands)		
Column capacity	384dots/line		
Printing speed	70mm/s		
Interface	USB+Bluetooth / USB+Wifi / USB+Wifi+Bluetooth		
Character size	ANK,Font A:1.5×3.0mm(12×24 dots)		
	Font B:1.1×2.1mm(9×17 dots)		
	simplified/traditional Chinese:3.0×3.0mm(24×24 dots)		
Barcode Character			
Extension character sheet	PC347(Standard Europe)/Katakana/PC850(Multilingual)/PC860(Portuguese)/PC863(Canadian-French)/PC865(Nordic)/West Europe/Greek/Hebrew/East Europe/Iran/WPC1252/PC866(Cyrillic#2)/PC852(Latin2)/PC858/IranII/Latvian/Arabic/PT151(1251)		
Barcode types	1D:UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) /CODE39/ITF/CODABAR/CODE93/CODE128 2D:QR CODE/PDF417		
Buffer			
Input buffer	32Kbytes		
NV Flash	64Kbytes		
Power			
Power adaptor	Output:DC 9V/2A		
Printer input	DC 9V/2A		
Battery	7.4V/2000mAh		
Physical characteristics			
Weight	0.215 KG		
Dimensions	107*76*50mm (D*W*H)		
Environmental Requirements			
Work environment	0~45℃, 10~80% RH		
Storage environment	-10~60℃, 10~90% RH(no condensation)		
Reliability			
Printer head life	50KM		
Driver		Windows/Linux/Android/Mac	